

Technical Specifications

FRAME	Specialized E5 aluminum, fully manipulated tubing, smooth weld, compact race design, 1-1/2" lower bearing, integrated heads
FORK	Specialized FACT carbon legs, aluminum crown and steerer, 1-1/2" lower bearing
HEADSET	1-1/8" upper and 1-1/2" lower Cr-Mo cartridge bearings integrated, w/ headset, 20mm cone spacer, w/ 20mm of spacers
STEM	Specialized EliteSet, 3D forged alloy, 12-degree, 4-position adjustable, 4-bolt, 31.8mm clamp
HANDLEBARS	New Specialized Tarmac Comp, alloy
TAPE	Specialized S-Wrap, w/ gel
FRONT BRAKE	Shimano 105
REAR BRAKE	Shimano 105
FRONT DERAILLEUR	Shimano 105
REAR DERAILLEUR	Shimano 105
SHIFT LEVERS	Shimano 105 STI, 10-speed
CASSETTE	Shimano 105, 10-speed, 11-28t
CHAIN	New Shimano Tiagra 10-speed
CRANKSET	Shimano 105 compact
CHAINRINGS	50/34
BOTTOM BRACKET	OS integrated, sealed bearings
PEDALS	Nylon flat test ride, loose ball, w/ reflectors
FRONT WHEEL	DT Axis 2.0

REAR WHEEL	DT Axis 2.0
FRONT TIRE	Specialized Esprit Sport w/ double BlackBelt, 60 TPI, wire bead, 700x23c
REAR TIRE	Specialized Esprit Sport w/ double BlackBelt, 60 TPI, wire bead, 700x23c
INNER TUBES	Lightweight, presta
SADDLE	Body Geometry Riva Road
SEATPOST	New Specialized Sport, alloy, 27.2mm
SEAT BINDER	Alloy, 31.8mm
NOTES	Chainstay protector, chain catcher, derailleur hanger, clear coat, owners manual

Allez Comp 105 Compact Bike Geometry

Size	49	52	54	56	58	61	64
B-B Drop	71.5mm	71.5mm	69mm	69mm	67.5mm	67.5mm	67.5mm
Chain-Stay Length	405mm	405mm	405mm	405mm	407mm	410mm	410mm
Crank Length	170mm	170mm	172.5mm	172.5mm	175mm	175mm	175mm
Fork Rake	45mm	45mm	45mm	43mm	43mm	43mm	43mm
Front-Center	576mm	576mm	583mm	591mm	605mm	613mm	617mm
Handle-Bar Width	400mm	420mm	420mm	420mm	440mm	440mm	440mm
Head-Tube Angle	72.25°	73°	73°	73.5°	73.5°	74°	74°

Head-Tube Length	100mm	120mm	145mm	170mm	205mm	230mm	250mm
Reach	385mm	385mm	385mm	392mm	397mm	402mm	401mm
Seat-Post Length	300mm	300mm	350mm	350mm	350mm	350mm	350mm
Seat-Tube Angle	75.5°	74°	73.5°	73.25°	73°	72.5°	72.5°
Seat-Tube Length, B-B Center to Top	460mm	490mm	510mm	530mm	550mm	580mm	620mm
Stack	505mm	527mm	548mm	575mm	607mm	632mm	652mm
Stand-Over Height	737mm	777mm	798mm	816mm	836mm	863mm	892mm
Stem Length	75mm	90mm	100mm	100mm	110mm	110mm	120mm
Top-Tube Length, Horizontal	518mm	537mm	548mm	565mm	582mm	600mm	605mm
Trail	62mm	57mm	57mm	56mm	56mm	53mm	53mm
Wheelbase	970mm	970mm	9				